


Specifications



MODELS	GL™-4		GL™-8		GL™-10		GL™-12	
MEASUREMENTS	Metric	US	Metric	US	Metric	US	Metric	US
A Height - stowed ^{1, 2, 3}	1.72 m	5 ft 7.5 in	1.72 m	5 ft 7.5 in	2 m	6 ft 6.5 in	2.13 m	7 ft 7 in
maximum forks down	1.30 m	4 ft 1.5 in	2.50 m	8 ft 3 in	3.01 m	9 ft 10.5 in	3.66 m	12 ft
maximum forks up	1.80 m	5 ft 11 in	3.10 m	10 ft .5 in	3.56 m	11 ft 8 in	4.20 m	13 ft 9.5 in
minimum forks down	9 cm	3.5 in	9 cm	3.5 in	5 cm	2 in	5 cm	2 in
STANDARD BASE								
B Length - stowed	30 cm	1 ft	30 cm	1 ft	—	—	—	—
operating	88 cm	2 ft 10.75 in	88 cm	2 ft 10.75 in	—	—	—	—
C Width: outside	63 cm	2 ft .75 in	63 cm	2 ft .75 in	—	—	—	—
Weight - standard caster options	51 kg	113 lbs	60 kg	132 lbs	—	—	—	—
pneumatic caster options	53 kg	117 lbs	62 kg	136 lbs	—	—	—	—
STRADDLE BASE								
Length - stowed	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in	49 cm	1 ft 7.25 in
operating	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in	1.09 m	3 ft 7 in
Width - stowed ⁴	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in
maximum ⁴	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in
maximum inside	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft
Weight - standard caster options	57 kg	126 lbs	66 kg	145 lbs	68 kg	149 lbs	70 kg	154 lbs
pneumatic caster options	59 kg	130 lbs	68 kg	149 lbs	69 kg	153 lbs	72 kg	158 lbs
4-point caster option	63 kg	139 lbs	72 kg	158 lbs	73 kg	162 lbs	76 kg	167 lbs
COUNTERWEIGHT BASE								
Length - operating	72 cm	2 ft 4.5 in	72 cm	2 ft 4.5 in	72 cm	2 ft 4.5 in	—	—
Width - stowed ⁴	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	73 cm	2 ft 4.75 in	—	—
maximum ⁴	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	1.10 m	3 ft 7.5 in	—	—
maximum inside	91 cm	3 ft	91 cm	3 ft	91 cm	3 ft	—	—
Weight - standard caster options	178 kg	392 lbs	186 kg	411 lbs	196 kg	433 lbs	—	—
PRODUCTIVITY								
Load height minimum	9 cm	3.5 in	9 cm	3.5 in	9 cm	3.5 in	9 cm	3.5 in
Ground clearance - centre ^{1, 2, 3}	2 cm	.75 in	2 cm	.75 in	2 cm	.75 in	2 cm	.75 in
Average cranks - standard winch	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft	38/m	11.5/ft
electric winch	5 cm/sec	2 in/sec	5 cm/sec	2 in/sec	5 cm/sec	2 in/sec	5 cm/sec	2 in/sec
Fork length	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in	57 cm	1 ft 10.5 in
Fork width	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in	52 cm	1 ft 8.5 in
Load platform length	58 cm	1 ft 11 in	58 cm	1 ft 11 in	58 cm	1 ft 11 in	58 cm	1 ft 11 in
Load platform width	56 cm	1 ft 10 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in	56 cm	1 ft 10 in
Load capacity at								
30 cm (12 in) load centre	227 kg	500 lbs	181 kg	400 lbs	159 kg	350 lbs	159 kg	350 lbs
Boom length	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in	51 cm	20.19 in
Boom attachment points	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in	34/48 cm	13.25/19 in
POWER								
Power source	reversible standard winch or electric winch							

¹ The 25 cm (10 in) pneumatic rear wheel option will add 2.5 cm (1 in) to these specifications.

² The counterweight base will add 2.5 cm (1 in) to these specifications.

³ The 4-point caster option B will add 2.5 cm (1 in) to these specifications.

⁴ Outside dimensions.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

FORK OPTIONS

- Standard forks
- Load platform
- Boom

POWER OPTIONS

- Standard winch
- Electric winch

BASE OPTIONS

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

WHEEL/CASTER OPTIONS

Straddle and standard base

- 20 cm (8 in) non-marking rear wheels
- Pneumatic rear tyre option
- 5 cm (2 in) dual wheel front swivel casters

Counterweight base

- 12 cm (5 in) rear swivel casters with side brakes
- 10 cm (4 in) fixed front wheels

Straddle base

- 4 point caster option

STANDARD FEATURES

MEASUREMENTS

GL™-4

- 1.80 m (5 ft 11 in) maximum lift height
- Up to 227 kg (500 lb) load capacity

GL™-8

- 3.10 m (10 ft .5 in) maximum lift height
- Up to 181 kg (400 lb) load capacity

GL™-10

- 3.56 m (11 ft 8 in) maximum lift height
- Up to 159 kg (350 lb) load capacity

GL™-12

- 4.20 m (13 ft 9.5 in) maximum lift height
- Up to 159 kg (350 lb) load capacity

PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminium construction
- Single door access
- Durable standard steel forks
- 20 cm (8 in) non-marking rear wheels and 5 cm (2 in) dual wheel front swivel casters (standard and straddle base only)

STANDARD FEATURES cont.

PRODUCTIVITY cont.

- 12.7 cm (5 in) rear swivel casters with side brakes and 10 cm (4 in) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

POWER

- Standard winch
- Reversible winch handle for easy storage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Load platform
- Boom
- Aluminium ladder (standard and straddle base only)
- Pneumatic rear tyres (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options

POWER

- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle base

UK

Millennium House
Brunel Drive
Newark NG24 2DE
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-25

Spain

Gaià 31, Pol. Ind. Plá d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Importgatan 17
422 46 Hisings Backa
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 90 20

Middle East

Terex Middle East
PO Box 282325, Dubai
U.A.E.
Tel: +971 4 885 8030
Fax: +971 4 885 6364
Email: awp.infome@terex.com

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, WA
USA 98073-9730
Tel: +1 425 881-1800
Fax: +1 425 883-3475

Email: AWP-InfoEurope@terex.com

Distributed By: